HAMMERHEAD. STILL TOUGH. STILL TRUSTED.





TRENCHLESS EQUIPMENT

SUPERIOR POWER FOR THE TOUGHEST OF TRENCHLESS PROJECTS

HYDROGUIDE® HG20

HAMMERHEAD® HYDROGUIDE® HG20

BUILT FOR TOUGH PIPE BURSTING JOBS





SUPERIOR POWER FOR ALL THE REALLY TOUGH JOBS.

The HydroGuide® HG20 winch has a compact design that increases maneuverability, simplifies transport and allows setup in tight areas. With 40,000 lbs (178 KN) of pull, the HG20 has the power to handle longer and larger pipe bursting 6 – 30"(150 – 750 mm) diameter pipe, slip lining, pipe pulling, cable pulling and swage lining jobs.

Like all HammerHead winches, the HG20 provides continuous tension on the cable while adjusting the line speed automatically.

DESIGNED FOR THE TRENCHLESS INDUSTRY.

Designed specifically for the trenchless industry, the HG20 can perform pipe bursting, slip lining, swage lining, cable and pipe pulling projects.

The solid dual capstan design offers constant pulling force over the entire cable length and helps reduce cable wear.

A proven bullwheel and planetary drive system provides superior reliability and performance on the job, where it counts.

EQUIPMENT SPECIFICATIONS

	Rig Size L/W/H – in (m)	159/81/66 (404/206/168)
20	Weight – lb (kg)*	7,000 (3,175)*
Ę	Max. pulling force – tons (t)	20 (18.1)
	Engine – HP (kw)	36 (26.5)
'DROGUIDE®	Engine manufacturer/model	Kubota V1505, Diesel
J.	Cooling system	Water cooled
ŏ	Downrigger length – ft (m)	19 (5.79)
Ď	Cable diameter – in (mm)	.875 (22)
₹	Cable weight – lb (kg)	2,840 (1,288)
	Standard usable cable length - ft (m)	1,250 (381)

	Single planetary bullwheel design	Standard
RES	Multi position leveling jacks	Standard, manual (1 front, 2 rear)
L _R	Remote hydraulics	Standard
¥	Electric start	Standard
H	Max. usable cable capacity – ft (m)	2,000 (610)
	Downrigger mast extension	Optional

^{*}Weight without cable.

CALL 800.331.6653
FOR A FREE PROJECT CONSULTATION TODAY.



