

UTILICOR MTC100



KEY FEATURES/BENEFITS

PRECISE CUTS

Used with the SK line of mini skid steers, the MTC100 coring attachment cuts a hole up to 18 inches in diameter and 22 inches deep for minimal surface disruption.

FULLY ADJUSTABLE SPEED

Speed level is adjustable from zero to 280 rpm for enhanced control and productivity.

COST EFFICIENT

The simple, efficient keyhole coring process is field-proven and is approximately 50 percent less costly than traditional excavation repairs and disposal removal.

QUICK SETUP

The MTC100 is a hydraulic system with a quick connect auxiliary hookup, allowing the operator faster setup.

COMPACT POWER

This easily maneuverable package works productively in confined spaces, including sidewalks, where larger, truck-mounted machines couldn't fit.

INTRODUCING THE
**UTILICOR
MTC100**
ATTACHMENT

UTILICOR MTC100 SPECIFICATIONS

DIMENSIONS	U.S.	METRIC
Length	39 in	990.6 mm
Overall width	38 in	965.2 mm
Shell width	29 in	736.6 mm
Height	80 in	2032 mm
Weight, water tank empty	602 lb	273 kg
Weight, water tank full	762 lb	345.6 kg
CAPACITIES	U.S.	METRIC
Water tank	20 gal	75.7 L
Drum speed	250/280 rpm @ 13/15 gpm	
Core drum diameter	Up to 8 to 18 in	Up to 203 to 305 mm
Coring depth, max	22 in	558.8 mm
Coring stroke, max	26 in	660.4 mm