

MAXI RIG TOOLING & ACCESSORIES CATALOG

VOLUME 1

888-660-0793 RadiusHDD.com

RADIUS HAS PRODUCED LARGE PILOT TOOLS & ROCK BITS FOR MAXI RIGS FOR OVER 10 YEARS WITH GREAT SUCCESS.

Radius HDD Tools has risen to become a leading supplier of quality HDD tools to drilling professionals around the world. Our support and commitment to HDD contractors who count on us continues to drive every aspect of our company.

RADIUS MAXI RIG TOOLING & SUPPLIES

While a large number of our customers own both class of machines, we understand very well the unique requirements and challenges of large rig operations. We have organized the most comprehensive collection of tools, supplies, and accessories specifically for large rig operators and pipeline contractors. Maxi tool and reamer repairs, custom subs, and manufacturing services are also available.

RADIUS MAXI JOB SITE SERVICES

Our dedicated "Job Site Service Department" will manage the transport, delivery and logistics of items such as, pallets of mud, hardwood mats, mudmotors, pipe rollers, consignment tool and supply lockers, restroom facilities, and erosion control products. Call us today to discuss the requirements of your project and how we can help. Like you, we understand that success is all about up-time and efficiency.

Lastly, and probably most importantly, is the team of Radius professionals who are available most hours of the day or night in their effort to support our customers.



TABLE OF CONTENTS

| Threaded Subs & Adapters | 5 |
|--------------------------------|----|
| Drive Chucks | 6 |
| Wireline Supplies | 7 |
| Sonde Housings | 8 |
| Pilot Tools | 10 |
| Rock Bits & Blade Adaptors | 11 |
| Bolt-On Housings & Dirt Blades | 12 |
| Drill Pipe | 12 |
| Reamers | 14 |
| Hole Openers | 16 |
| Reamer & Hole Opener Parts | 17 |
| Pulling Supplies | 18 |
| Repair Parts and Maintenance | 19 |
| Job Site & Safety Supplies | 20 |
| Rig Notes | 23 |

Radius Maxi Rig Tooling and Supplies

RADIUS IS YOUR GO-TO SOURCE FOR MAXI RIG CONNECTIONS.

Thread Identification Kit

The Radius thread ID kit makes it easy to know exactly what thread you have, or more importantly, which thread you need.

How To Order Custom Subs

Identify the

threads

vou need

In many cases custom sub orders are vital, a machine is down or a timeline is critical. We understand there is no room for errors or delays. Following the steps below will assist us in getting your custom sub right the first time – on time.

Verify

the gender

vou need

Determine OAL or Shoulder to Shoulder length Determine the outside diameter

Call us at 888-660-0793

BUILD YOUR SUB TODAX. GET IT TOMORNOW Image: State of the state o

BUILD THE SUB YOU NEED ONLINE AT RADIUSHDD.COM

SAME DAY SHIPPING AVAILABLE WHEN TIME IS CRITICAL!

COMMON HDD MAXI THREADS

| | Туре | Material | PI | N Dim | Box | Dim | Thre | ead |
|--------------------------------|-------|----------|--------|--------|-------|--------|-------|------|
| | | OD | Pin L | Pin ID | Box L | Box ID | Taper | TPI |
| 2.875" IF | NC-31 | 4.125 " | 3.5" | 3.385 | 3.75" | 2.5 | 2" | 4" |
| 2875" IF Double Shoulder | DS-31 | 4.125" | 3.5" | 3.385 | 3.75" | 2.5 | 2" | 4" |
| 3.5" IF | NC-38 | 4.75" | 4" | 4.000 | 4.25" | 3.25 | 2" | 4" |
| 3.5" IF Double Shoulder | DS-38 | 4.75" | 4" | 4.000 | 4.25" | 3.25 | 2" | 4" |
| 4.5" IF | NC-46 | 6" | 4.5" | 4.828 | 3.75" | 3.5 | 2" | 4" |
| 4" Full Hole | DS-40 | 5.25" | 4.5" | 4.270 | 4.75" | 3.25 | 2" | 4" |
| 5.5" Full Hole | NC-55 | 7" | 5" | 5.828 | 5.5" | 4.25 | 2" | 4" |
| 5.5" Full Hole Double Shoulder | DS-55 | 7" | 5" | 5.828 | 5.5" | 4.25 | 2" | 4" |
| 6.625" Full Hole | NC-65 | 8" | 5" | 6.740 | 5.5" | 5.5 | 2" | 4" |
| 4.5" API REG | API | 5.25" | 4.25" | 5.515 | 5" | 3.375 | 3" | 5" |
| 6.625" API REG | API | 7.75" | 5" | 5.975 | 5.25" | 4.75 | 2" | 4" |
| 7.625" API REG | API | 8.875" | 5.25" | 6.975 | 5.5" | 5.25 | 3" | 4" |
| 8.625" API REG | API | 10" | 5.375" | 7.951 | 6.25" | 6.625 | 3" | 4" |
| 3.5" Firestick (1000) | 0EM | 4.5" | 3.5" | 3.875 | 3.5" | | | 3.5" |
| 3.27"-4" DW (JT7020/8020/100) | OEM | 4" | 5.25" | 3.312 | 5.25" | | | 4" |



COMMON HDD SUB AND ADAPTERS

| | FS1000 | FS900 | FS800 | 3.5" IF | 2.875" IF | 3.5" REG | 3.5" IF | 4.5" REG | 4.5" IF | 5.5" FH | 6.625" FH | 4" Full Hole |
|--------------------------------|--------|-------|-------|------------|--------------|-------------|------------|-------------|------------|------------|--------------|-----------------|
| 2.875" IF (Internal Flush) | x | X | X | Х | X | Х | | | | | | |
| 2.875" IF DS (Double Shoulder) | X | Х | X | Х | X | Х | | | | | | |
| 3.5" IF | | | | | X | Х | X | X | Х | | | |
| 3.5" IF DS | | | | | X | Х | X | X | Х | | | |
| 4.5" IF | | | | | | Х | X | X | Х | Х | X | |
| 4" FH (Full Hole) | | | | | | | | | | | | Х |
| 5.5" FH | | | | | | | | | Х | | X | |
| 5.5" FH DS | | | | | | | | | Х | | X | |
| 6.625" IF | | | | | | | | | | X | X | |

DRIVE CHUCKS & SAVER SUBS

Connecting the kelly to the pipe is critical. Radius drive chucks and saver subs are built to the exact specifications for your rig using heat treated alloys for maximum strength and durability. Radius also offers drive chucks with water swivels and wireline capabilities.

| American A | American Augers | | | | | |
|------------|-----------------|---------------------|------------|--|--|--|
| Part # | Rig Size | Common Thread Type | Connection | | | |
| 953-0378 | DD110 / DD110S | 2.875" IF Box x Pin | Kelly | | | |
| 953-0379 | DD155TS | 4.5" IF Box x Pin | Kelly | | | |
| 953-0379 | DD-220T | 4.5" IF Box x Pin | Kelly | | | |
| 953-0380 | DD-440 / DD440T | 6.625" FH Box x Pin | Kelly | | | |
| 953-0380 | DD-625 | 6.625" FH Box x Pin | Kelly | | | |
| 953-0380 | DD1100RS | 6.625" FH Box x Pin | Kelly | | | |

| Barbco | Barbco | | | | | | |
|----------|------------|--------------------|------------|--|--|--|--|
| Part # | Rig Size | Common Thread Type | Connection | | | | |
| 953-0387 | BD100-20SC | FSI 1000 Box x Pin | Kelly | | | | |
| 953-0387 | BD120-20SC | FSI 1000 Box x Pin | Kelly | | | | |
| 953-0388 | BD250-TK | 3.5" IF Box x Pin | Kelly | | | | |
| 953-0379 | BD500-TK | 4.5" IF Box x Pin | Kelly | | | | |
| 953-0389 | BD750-TK | 5.5" IF Box x Pin | Kelly | | | | |

| Ditch Witch | | | | | |
|-------------|----------|--|------------|--|--|
| Part # | Rig Size | Common Thread Type | Connection | | |
| 953-0041 | JT100 | 3.27-4 Ditch Witch Drill Pipe (Small Flange) | Flange | | |
| 953-0367 | JT100 | 3.27-4 Ditch Witch Drill Pipe (Large Flange) | Flange | | |
| 953-0268 | AT100 | 3.44-4 Ditch Witch Drill Pipe | Flange | | |

| Universal | | | | | |
|-----------|-------------|--------------------------------|------------|--|--|
| Part # | Rig Size | Common Thread Type | Connection | | |
| 953-0383 | UNI 90x120 | FS1 800 | Flange | | |
| 953-0384 | UNI 90x120 | FS1 1000 | Flange | | |
| 953-0390 | UNI 100x120 | FS1 1000 | Flange | | |
| 953-0385 | UNI 100x120 | 3.5" HXT (FSII) | Flange | | |
| 953-0386 | UNI 120x180 | DS-40 (4" Full Hole) Box x Pin | Kelly | | |
| 953-0386 | UNI 160x240 | DS-40 (4" Full Hole) Box x Pin | Kelly | | |
| 953-0379 | UNI 220x240 | 4.5" IF Box x Pin | Kelly | | |

| Vermeer | | | | | | |
|----------|-----------------------|---------------------|------------|--|--|--|
| Part # | Rig Size | Common Thread Type | Connection | | | |
| 953-0195 | 100x120 SII / 100x140 | FS 1000 | Flange | | | |
| 953-0381 | 100x120 SII / 100x140 | 3.5" HXT (FSII) | Flange | | | |
| 953-0379 | 200x300 | 4.5" IF Box x Pin | Kelly | | | |
| 953-0382 | 330x500 | DS 55 Box x Pin | Kelly | | | |
| 953-0380 | 500x500 | 6.625" FH Box x Pin | Kelly | | | |
| 953-0380 | 750x900 | 6.625" FH Box x Pin | Kelly | | | |
| 953-0380 | 1000x900 | 6.625" FH Box x Pin | Kelly | | | |
| 953-0380 | 1320x900 | 6.625" FH Box x Pin | Kelly | | | |





WIRELINE SUPPLIES



954-0438



954-0459



954-0460



954-0461





954-0463, 954-0464 954-0465

| Wireline Su | Wireline Supplies | | | | |
|-------------|---|--|--|--|--|
| Part # | Description | | | | |
| 954-0438 | Wireline Adapter Tool Kit | | | | |
| 954-0459 | Wireline Heat Shrink Tubing - HIM Black HS .375" x 4ft | | | | |
| 954-0460 | Wireline Wire - 10-19 Strand Copper Clad Wire, 1000ft Rolls | | | | |
| 954-0461 | Nicopress Aluminum Wireline Connectors (Side by Side) FW-2"-3.75" | | | | |
| 954-0462 | Wireline Crimping Tool #51 - for Aluminum Wireline Connectors | | | | |
| | (for use with Side by Side Crimps) | | | | |
| 954-0463 | Nylon Wireline Spider - for 2.875" IF Pipe | | | | |
| 954-0464 | Nylon Wireline Spider - for 3.5" IF Pipe | | | | |
| 954-0465 | Nylon Wireline Spider - for 4.5" IF / 5.5" FULL HOLE Pipe | | | | |



THE MOST POPULAR SONDE HOUSING AMONG DRILLERS.

When it comes to large diameter sonde housings, no one offers more options than Radius.

Strong, dependable and built to last, big rig operators depend on our sonde housings every day to perform in even the toughest ground conditions. All Radius sonde housings are manufactured from a proprietary heat treated alloy to ensure both strength and durability.

Radius End Load Housings


The Radius end load sonde housing offers complete sonde protection, maximum fluid flow for use with mud motors and is wireline capable. But perhaps the most popular feature of the Radius end load sonde housing is the side access window. Only 2 inches in length, this patented feature poses no threat of sonde loss. It does allow for simplified sonde clocking, easy check of temperature indicator, and most importantly, aids in the removal of the sonde by way of flushing the cavity and pushing the transmitter out the rear of the housing. This last feature is only understood by drillers who know the difficulty of removing a sonde from a mud-filled end load housing.

All Radius End Load Housings feature:

- High Flow capacity for use with mud motors
- Wireline capabilities
- Compatible with both 15" & 19" DCI sondes



| Radius End Load Housings | | | | | |
|--------------------------|-----------|--|--|--|--|
| Part # | Rig Class | Description | | | |
| 951-4501 | 80-100k | 4.5" End Load Housing (2.875" IF Box x 2.875" Reg Box) add it above the 951-5001 | | | |
| 951-5001 | 100-200k | 5" OD End Load Housing (3.5" IF Box x 3.5" Reg Box) | | | |
| 951-6501 | 200-350k | 6.5" OD End Load Housing (4.5" IF Box x 4.5" Reg Box) | | | |
| 951-8001 | 350k+ | 9" OD End Load Housing (6.625" Reg Box x 6.625" Full Hole Box) | | | |
| 951-8002 | 350k+ | 9" OD End Load Housing (6.625" IF Box x Box) | | | |




Radius Rock Housings

Definitely the most popular sonde housing among drillers, the Radius rock housing combines the strength and protection of an end load housing with the convenience and access of a side load unit. The patented reduced window design allows the housing to withstand much higher torque loads than common side load housings. This housing was specifically designed for drilling in tough conditions.

All Radius Rock Housings feature:

- High Flow capacity for use with mud motors
- Wireline capabilities
- Compatible with both 15" & 19" DCI sondes as well as Subsite and other popular transmitters





| Radius Ro | Radius Rock Housings | | | | |
|-----------|----------------------|---|--|--|--|
| Part # | Rig Class | Description | | | |
| 951-4500 | 80-100k | 4.25" OD Rock Houisng (2.875" Reg Box x 4.5" Radus Pin) | | | |
| 951-5005 | 100-200k | 5" OD Rock Housing (3.5" IF Box x 3.5" Reg Box) | | | |
| 951-5006 | 100-200k | 5" OD Rock Housing (3.5" Reg Box x 3.5" Reg Box) | | | |
| 951-6505 | 200-350k | 6.5" OD Rock Housing (4.5" IF Box x 4.5" Reg Box) | | | |

950-1042

950-1043

9 875"

12.25"

Radius Maxi Rig Tooling and Supplies

PILOT TOOLS

Radius Cobble Bits

Ideal for loose rock, cobble and softer rock formations, the Radius cobble bit is also a good alternative in constantly changing ground conditions. Carbide buttons and hard facing help protect the tool while at work.

| Cobble Bits | | | | | | |
|-------------|-----------|------------|-----------------|----------------|--|--|
| Part # | Rig Class | Pilot Hole | Description | Connection | | |
| 950-4505 | 80-100k | 6" | 4.5" Cobble Bit | 2.875" Reg Pin | | |
| 950-5005 | 100-200k | 7" | 5" Cobble Bit | 3.5" Reg Pin | | |

Single Roller Cone Bit

Another popular option for drilling in solid rock conditions is the Radius Single Roller Cone bit (SRC). While not very effective in soft soil or loose ground, the SRC bit performs well in solid rock formations up to 20,000-25,000 psi.

| | Single Roller Cone bits | | | | | | | |
|--|---|--|--|-----------------------------|----------------|--|--|--|
| | Part # Rig Class Pilot Hole Desc | | | Description | Connection | | | |
| | 950-4501 80-100k 7" 950-5003 100-200k 9-10" | | | 4.5" Single Roller Cone Bit | 2.875" Reg Pin | | | |
| | | | | 5" Single Roller Cone Bit | 3.5" Reg Pin | | | |

Tricone & PDC bits

For mud motors and extreme hard conditions Radius features several lines of new tricone and Polycrystalline Diamond Compact (PDC) bits. By working with both drillers and US manufactures Radius has organized a line of tricones and PDC bits that deliver increased productivity and durability.

| Tungsten (| Tungsten Carbide Insert (TCI) TriCone Bits | | | | | |
|------------|--|-------------------------------|--|--|--|--|
| Part # | Tool Diameter | Description | | | | |
| 950-1011 | 6.5" | 3.5" Reg Pin | | | | |
| 950-1012 | 6.75" | 3.5" Reg Pin | | | | |
| 950-1013 | 7.875" | 4.5" Reg Pin | | | | |
| 950-1014 | 8.5" | 4.5" Reg Pin | | | | |
| 950-1015 | 9.875" | 6.625" Reg Pin | | | | |
| 950-1016 | 12.25" | 6.625" Reg Pin | | | | |
| Mill Tooth | Tricone Bits | | | | | |
| Part # | Tool Diameter | Description | | | | |
| 950-1017 | 6.5" | 3.5" Reg Pin | | | | |
| 950-1018 | 6.75" | 3.5" Reg Pin | | | | |
| 950-1019 | 7.875" | 4.5" Reg Pin | | | | |
| 950-1022 | 8.5" | 4.5" Reg Pin | | | | |
| 950-1020 | 9.875" | 6.625" Reg Pin | | | | |
| Polycrysta | Polycrystaline Diamond Compact (PDC) Bits | | | | | |
| Part # | Tool Diameter | Description | | | | |
| 950-1039 | 7.875" | 4.5" Reg Pin, 5 Blade PDC Bit | | | | |
| 050 4040 | | | | | | |
| 950-1040 | 8.5" | 4.5" Reg Pin, 5 Blade PDC Bit | | | | |

6.625" Reg Pin, 6 Blade PDC Bit

6.625" Reg Pin, 6 Blade PDC Bit



Cobble Bit



Single Roller Cone Bit







TCI Tri-Cone Bit













920-8000

ROCK BITS

Rock tools are indeed the flagship of the Radius product line. We offer a wider selection than any aftermarket supplier and even some OEM's. And no one builds a better bit. Controlled cutting. Unsurpassed durability. Radius continues to be the best choice for HDD Professionals.

Radius Rock Bits

Our most versatile tool offers maxi rig operators greater steering and control in any type of soil conditions while letting you navigate loose rock and solid rock conditions up to 15,000 psi. Features that separate the Radius rock bit from other lesser designs include over sized carbide buttons that offer maximum durability while grinding cuttings in to smaller, more float-able size and a proprietary body geometry that provides greater control during the drill and improved responsiveness while carving or steering.

| Rock Bits | | | | | | |
|-----------|--------------------|------------|----------------------|-----------------|--|--|
| Part # | Rig Class | Pilot Hole | Description | Connection | | |
| 950-4500 | 0-5000 100-200k 8" | | 4.5" Radius Rock Bit | 2.875" Reg Pin | | |
| 950-5000 | | | 5" Radius Rock Bit | 3.5" Reg Pin | | |
| 950-5001 | | | 5" Radius Rock Bit | 3.5" IF Pin | | |
| 950-6500 | 200-350k | 9-10" | 6.5" Radius Rock Bit | 4.5" Reg Pin | | |
| 950-8000 | 350k+ | 12-14" | 8.5" Brutus Bit | 6.625" Reg Pin | | |
| 950-8001 | 350k+ | 12-14" | 8.5" Brutus Bit | 4.5" IF Reg Pin | | |



BLADE ADAPTORS

For conditions that do not require the use of a rock bit, Radius provides a wide selection of blade adapters and dirt tools designed to work on most any type of maxi sonde housing. Using blade adapters can extend the life of your rock tooling and increase steering performance in certain ground types.

| Blade Adap | Blade Adapters | | | | |
|------------|----------------|----------------------------|---|--|--|
| Part # | Rig Class | Description | Connection | | |
| 952-0089 | 100-200k | 5" OD Dirt Blade Adapter | 3.5" Reg Pin x 6 BOLT Vermeer .625"-11 | | |
| 952-0090 | 100-200k | 5" OD Dirt Blade Adapter | 3.5" IF Pin x 6 BOLT Vermeer .625"-11 | | |
| 952-0137 | 100-200k | 5" OD Dirt Blade Adapter | 3.5" Reg Pin x 6 BOLT Vermeer .75"-10 | | |
| 952-0091 | 200-350k | 6.5" OD Dirt Blade Adapter | 4.5" Reg Pin x 6 BOLT Vermeer .625"-11 | | |
| 952-0138 | 200-350k | 6.5" OD Dirt Blade Adapter | 4.5" Reg Pin x 6 BOLT Vermeer .75"-10 | | |
| 952-0096 | 100-200k | 5" OD Dirt Blade Adapter | 3.5" Reg Pin x 6 BOLT Ditch Witch 20mm SHCS | | |
| 952-0126 | 200-350k | 6.5" OD Dirt Blade Adapter | 4.5" Reg Pin x 6 BOLT Ditch Witch 20mm SHCS | | |

Order Your Way: 888-660-0793 • RadiusHDD.com

BOLT-ON HOUSINGS & DIRT BLADES

When it comes to large diameter sonde housings, no one offers more options than Radius. Strong, dependable and built to last, big rig operators depend on our sonde housings every day to perform in even the toughest ground conditions.

| | Dirt Housing | Dirt Housings | | | | |
|----------|--------------|---------------|--|--|--|--|
| Part # R | | Rig Class | Description | | | |
| | 952-0006 | 80k-150k | 4.5" OD Side Load Dirt Housing (2.875" Reg Box x 6 BOLT Vermeer* 5/8" - 11 SHCS) | | | |
| - | 952-0135 | 150-200k | 5" OD Side Load Dirt Housing (3.5" IF Box x 6 BOLT Vermeer* 3/4" - 10 SHCS) | | | |
| | 952-0136 | 200-350k | 6" OD Side Load Dirt Housing (4.5" IF Box x 6 BOLT Vermeer* 3/4" - 10 SHCS) | | | |

| Dirt Blades - Vermeer* 6 bolt 5/8 - 11 Bolt Pattern | | | | | | |
|---|-----------|------------------------------|--|--|--|--|
| Part # | Rig Class | Description | | | | |
| 952-0047 | 100-200k | 1" x 6" Rubble / Hard Faced | | | | |
| 952-0133 | 100-200k | 1" x 8" Rubble / Hard Faced | | | | |
| 952-0139 | 100-200k | 1" x 10" Rubble / Hard Faced | | | | |

| Dirt Blade | Dirt Blades - Vermeer* 6 bolt 3/4 - 10 Bolt Pattern | | | | | | | |
|-------------------|---|------------------------------|--|--|--|--|--|--|
| Part # | Rig Class | Description | | | | | | |
| 952-0140 | 200k+ | 1" x 6" Rubble / Hard Faced | | | | | | |
| 952-0119 | 200k+ | 1" x 8" Rubble / Hard Faced | | | | | | |
| 952-0141 | 200k+ | 1" x 10" Rubble / Hard Faced | | | | | | |
| 952-0142 | 200k+ | 1" x 12" Rubble / Hard Faced | | | | | | |

Larger sizes and custom blades are available. Call for details.

* Vermeer compatible bolt pattern

DRILL PIPE

Radius has negotiated dealer agreements with a number of leading pipe suppliers in both the HDD and oilfield industries. This allows us to offer an unmatched number of options when it comes to buying drill pipe. From new and used double white band to industry inspected yellow band used pipe – one rod or a truck load, let us help keep your rod cost in line.

| Drill Pipe | | |
|------------|-------------|---|
| Part # | Description | |
| PIP-0021 | 15ft. | 7020/8020/JT100 Drill Pipe (3.27-4 DW comp) |
| PIP-0027 | 20ft. | DD 100 x 120 / DD 100 x 140 Drill Pipe (FS-1000 comp) |
| PIP-0026 | 20ft. | 2.875" IF Double Shoulder Drill Pipe |
| PIP-0020 | 15ft. | 2.875" IF Drill Pipe |
| PIP-0022 | 20ft. | 2.875" IF Drill Pipe |
| PIP-0028 | 15ft. | 3.5" IF Drill Pipe |
| PIP-0029 | 20ft. | 3.5" IF Drill Pipe |
| PIP-0030 | 20ft. | 4.5" IF Drill Pipe |
| PIP-0024 | 20ft. | 4" Full Hole Double Shoulder |
| PIP-0031 | 31ft. | 5.5" Full Hole |
| PIP-0032 | 31ft. | 5.5" Full Hole Double Shoulder |



RADIUS IS A LEADING SOURCE FOR NEW AND RE-USED MAXI RIG PIPE

Radius Maxi Rig Tooling and Supplies

REAMERS

Radius designs and manufactures the largest selection of heavy duty reamers and hole openers specifically for maxi rig operations. Maxi projects require reamers engineered to a high level of quality. All reamers and hole opener shafts are machined from a 4140 or 4145 heat treated alloy for maximum thread and torque strength. A team of experienced welders understand preheating, cooling and other processes which are required to properly weld various types of metals that are used in all hole openers and reamers. Additionally, tungsten carbide and hard facing are applied to all heavy wear areas of each tool to maximize its performance and durability.

| | 1000 C | | Contraction of the second | | Arra |
|-------------|----------|----------|---------------------------|-----------|------|
| Barrel | | | | | |
| Shaft Size | 4.75" OD | 6.5" OD | 7.25" OD | 8.75" OD | |
| Thread Type | 3.5" IF | 4.5" IF | 5.5" FH | 6.625" FH | |
| 12" | 956-0282 | 956-0290 | | • | |
| 16" | 956-0283 | 956-0291 | | | |
| 20" | 956-0284 | 956-0292 | 956-0301 | 956-0310 | |
| 24" | 956-0285 | 956-0293 | 956-0302 | 956-0311 | . 7 |
| 30" | 956-0286 | 956-0294 | 956-0303 | 956-0312 | |
| 36" | 956-0287 | 956-0295 | 956-0304 | 956-0313 | 2 |
| 42" | 956-0288 | 956-0296 | 956-0305 | 956-0314 | |
| 48" | 956-0289 | 956-0297 | 956-0306 | 956-0315 | |
| 54" | - | 956-0298 | 956-0307 | 956-0316 | |
| 60" | - | 956-0299 | 956-0308 | 956-0317 | |
| 72" | - | 956-0300 | 956-0309 | 956-0318 | |

Barrel Reamers

Barrel reamers can be run in tandem with a lead cutting reamer or alone as a compaction or swabbing tool. Radius barrel reamers are designed with front and rear fluid chambers to keep weight and fluid use to a minimum. Fluid ports are located on both ends of the reamer to allow bi-directional use to maximize the life of the tool, a heavy hatch pattern of hard-facing is applied to all wear surfaces. Carbide cutters on both faces assist with the hole development and to mix cuttings with drilling mud. Clean-out ports are located on each face as well for easy maintenance.

15

REAMERS CONTINUED

Flycutters

Designed for a variety of conditions from compact soils to soft rock. 3/4" or 1" rolled plate and cutter bars offer maximum cutter support and durability. Various removable nozzle configurations allow precise control over fluid volume and placement. 3/4" to 1" plasma cut structural components minimize deflection and offer increased suspension of cuttings & fluids for greater returns. Radius fly cutter reamers are available in single or bi-directional designs.

| Bi-Direction | Bi-Directional Flycutters | | | | | | | |
|---------------------|---------------------------|----------|----------|-----------|--|--|--|--|
| Shaft Size | 4.75" OD | 6.5" OD | 7.25" OD | 8.75" OD | | | | |
| Thread Type | 3.5" IF | 4.5" IF | 5.5" FH | 6.625" FH | | | | |
| 12" | 956-0247 | - | - | - | | | | |
| 16" | 956-0248 | 956-0255 | - | - | | | | |
| 20" | 956-0249 | 956-0256 | 956-0264 | 956-0273 | | | | |
| 24" | 956-0250 | 956-0257 | 956-0265 | 956-0274 | | | | |
| 30" | 956-0251 | 956-0258 | 956-0266 | 956-0275 | | | | |
| 36" | 956-0252 | 956-0178 | 956-0267 | 956-0276 | | | | |
| 42" | 956-0253 | 956-0259 | 956-0268 | 956-0277 | | | | |
| 48" | 956-0254 | 956-0260 | 956-0269 | 956-0278 | | | | |
| 54" | - | 956-0261 | 956-0270 | 956-0279 | | | | |
| 60" | - | 956-0262 | 956-0271 | 956-0280 | | | | |
| 72" | - | 956-0263 | 956-0272 | 956-0281 | | | | |

Stack Plate Reamers

Stack plate reamers offer many of the same design features of spiral fluted reamers but are available in larger diameters. Constructed with 1.25" plate stacks welded inside and out to offer unmatched durability and strength. Recent interior chamber designs have reduced the weight on many sizes by up to 20%.

| Stack-Plate | Stack-Plate | | | | | |
|-------------|-------------|----------|----------|-----------|--|--|
| Shaft Size | 5" OD | 6.5" OD | 7.25" OD | 8.75" OD | | |
| Thread Type | 3.5" IF | 4.5" IF | 5.5" FH | 6.625" FH | | |
| 12" | 956-0319 | - | - | - | | |
| 16" | 956-0032 | 956-0320 | - | - | | |
| 20" | 956-0034 | 956-0321 | 956-0327 | 956-0333 | | |
| 24" | 956-0035 | 956-0322 | 956-0328 | 956-0334 | | |
| 30" | 956-0038 | 956-0323 | 956-0329 | 956-0335 | | |
| 36" | 956-0041 | 956-0324 | 956-0330 | 956-0336 | | |
| 42" | - | 956-0325 | 956-0331 | 956-0337 | | |
| 48" | - | 956-0326 | 956-0332 | 956-0338 | | |



Radius Maxi Rig Tooling and Supplies

HOLE OPENERS

Maxi rig operators demand quality and performance. Radius understands there are no second chances on large jobs. Each of our hole openers are built from over-sized iron and multi-pass welds by a team of fabricators with a lifetime of experience in their craft.

The Radius "split-bit" hole openers are available in any size and can be assembled with a number of options including:

- New or used cone segments
- Mill tooth or TCI segments in a variety of grades
- Front centralizer
- Bi-directional cutters
- Fluid controls
- Shaft sizes (diameter & length)
- Thread connections or pulling eyes
- Numerous hard facing options

| Common Hole Opener Sizes | | | | | | | |
|--------------------------|----------|----------|----------|-----------|-----------------|--|--|
| Shaft Size | 4.75" OD | 6.5" OD | 7.25" OD | 8.75" OD | | | |
| Thread Type | 3.5" IF | 4.5" IF | 5.5" FH | 6.625" FH | | | |
| 16" | 956-0181 | | -// | - | 2 - H | | |
| 20" | 956-0182 | 956-0186 | | - () | Rest Harden | | |
| 24" | 956-0183 | 956-0187 | 956-0195 | 956-0203 | | | |
| 30" | 956-0184 | 956-0188 | 956-0196 | 956-0204 | | | |
| 36" | 956-0185 | 956-0189 | 956-0197 | 956-0205 | | | |
| 42" | - 2.8 | 956-0190 | 956-0198 | 956-0206 | | | |
| 48" | | 956-0191 | 956-0199 | 956-0207 | | | |
| 54" | | 956-0192 | 956-0200 | 956-0208 | | | |
| 60" | - 3.20 | 956-0193 | 956-0201 | 956-0209 | | | |
| 72" | - 2014 | 956-0194 | 956-0202 | 956-0210 | and all the and | | |



HOLE-OPENER & REAMER REPAIR COMPONENTS

Radius offers a complete selection of build and repair products for maintaining your fleet of reamers and hole openers. New and used cone segments, mill tooth, tungsten carbide insert (TCI), and most IADC grades are available with or without carbide nozzles. Reamer shafts and weld on cutters are also available.

| Threaded Reamer Shafts | | | | | |
|------------------------|------------------------------|-----------------------------|------------------------------|--------------------------------|--|
| Overall length | 3.5" IF Box x Box (4.75" OD) | 4.5" IF Box x Box (6.5" OD) | 5.5" FH Box x Box (7.25" OD) | 6.625" FH Box x Box (8.75" OD) | |
| 48" | RMS-0019 | RMS-0051 | RMS-0044 | RMS-0043 | |
| 60" | RMS-0020 | RMS-0023 | RMS-0045 | RMS-0026 | |
| 72" | RMS-0021 | RMS-0024 | RMS-0046 | RMS-0028 | |
| 84" | RMS-0022 | RMS-0002 | RMS-0047 | RMS-0029 | |
| 96" | RMS-0035 | RMS-0038 | RMS-0048 | RMS-0030 | |
| 108" | RMS-0036 | RMS-0039 | RMS-0049 | RMS-0041 | |
| 120" | RMS-0037 | RMS-0040 | RMS-0050 | RMS-0042 | |

| Weld-On Cutters | | | | | |
|-----------------|--|--------|-------|--------|---------|
| Part # | Description | Length | Width | Height | |
| 954-0079 | Weld-On Conicle / Angle Base - LARGE | 2.46" | 1.38" | 1.25" | - |
| 954-0078 | Weld-On Conicle / Angle Base - SMALL | 2.26" | 1.06" | 1.26" | A View |
| 954-0498 | Weld-On Conicle / Angle Base - EXTRA SMALL | 1.35" | 0.77" | 0.82" | 2975 |
| 954-0077 | Weld-On Shark Tool Cutter - LARGE | 2.36" | 0.72" | 2.17" | |
| 954-0076 | Weld-On Shark Tool Cutter - MEDIUM | 1.5" | 0.84" | 1.77" | |
| 954-0075 | Weld-On Shark Tool Cutter - SMALL | 1" | 0.5" | 1.25" | The the |
| 954-0072 | Weld-On Cutter Block - LARGE | 0.77" | 1.75" | 2.24" | |
| 954-0074 | Conical Tooth for LARGE Block | 0.77" | | 3.36" | |

| Single Rep | lacement Cone Segments | |
|------------|---|------------|
| Part # | Description | |
| 954-0586 | 7.875" TCI - Sealed Bearing Cutter Segment - NEW | A A A |
| 954-0068 | 8.5" TCI - Sealed Bearing Cutter Segment - NEW | |
| 954-0587 | 9.875" TCI - Sealed Bearing Cutter Segment - NEW | |
| 954-0398 | 12.25" TCI - Sealed Bearing Cutter Segment - NEW | |
| 954-0531 | 7.875" MILL TOOTH - Sealed Bearing Cutter Segment - NEW | |
| 954-0532 | 8.5" MILL TOOTH - Sealed Bearing Cutter Segment - NEW | |
| 954-0533 | 9.875" MILL TOOTH - Sealed Bearing Cutter Segment - NEW | Santa Land |
| 954-0397 | 12.25" MILL TOOTH - Sealed Bearing Cutter Segment - NEW | 33 |
| 954-0493 | 9" TCI RANDOM Bit Third - Sealed Bearing Cutter - NEW | |
| 954-0494 | 12.25" TCI RANDOM Bit Third - Sealed Bearing Cutter - NEW | |
| 954-0570 | 17.5" TCI RANDOM Bit Third - Sealed Bearing Cutter - NEW | |

PULLING SUPPLIES


| Polycam / | Polycam / Weld on Pullers | | | | | |
|-----------|---------------------------|------------------------------------|--|--|--|--|
| Part # | Size | Description | | | | |
| 954-0625 | 12" Polycam Puller | 650 Series Steel Pulling Head IPS | | | | |
| 954-0626 | 16" Polycam Puller | 650 Series Steel Pulling Head IPS | | | | |
| 954-0627 | 20" Polycam Puller | 650 Series Steel Pulling Head IPS | | | | |
| 954-0628 | 24" Polycam Puller | 650 Series Steel Pulling Head IPS | | | | |
| 954-0629 | 36" Polycam Puller | 650 Series Steel Pulling Head IPS | | | | |
| 954-0630 | 48" Polycam Puller | 650 Series Steel Pulling Head IPS | | | | |
| 954-0631 | 12" Polycam Puller | 651 Series Steel Pulling Head DIPS | | | | |
| 954-0632 | 16" Polycam Puller | 651 Series Steel Pulling Head DIPS | | | | |
| 954-0633 | 20" Polycam Puller | 651 Series Steel Pulling Head DIPS | | | | |
| 954-0634 | 24" Polycam Puller | 651 Series Steel Pulling Head DIPS | | | | |
| 954-0635 | 36" Polycam Puller | 651 Series Steel Pulling Head DIPS | | | | |
| 954-0636 | 48" Polycam Puller | 651 Series Steel Pulling Head DIPS | | | | |

| Pipe Rollers | Pipe Rollers | | | | |
|--------------|---------------------|----------------|--|--|--|
| Part # | Item | Size | | | |
| 954-0643 | Dual Roller | 4" x 16" Pipe | | | |
| 954-0642 | Large Single Roller | 12"x 30" Pipe | | | |
| 954-0727 | Goliath Pipe Roller | 30" x 48" Pipe | | | |


| Bolt Syle Sł | Bolt Syle Shackles | | | | | | | |
|--------------|--------------------|------|---------|--------|--------|--------|--------|-----------|
| Part # | Size A | Tons | Diam. B | C | D | E | F | Weight |
| 954-0112 | 1.375" | 13.5 | 1.5" | 5.312" | 2.125" | 3.25" | 3.5" | 13 lbs |
| 954-0622 | 1.5" | 17 | 1.625" | 5.687" | 2.312" | 3.5" | 3.75" | 16.5 lbs |
| 954-0623 | 1.75" | 25 | 2" | 7.062" | 2.875" | 4.25" | 4.875" | 29 lbs |
| 954-0624 | 2" | 35 | 2.25" | 7.75" | 3.312" | 4.875" | 5.437" | 43 lbs |
| 954-0637 | 2.25" | 45 | 2.5" | 9.25" | 3.625" | 5.25" | 5.5" | 59.5 lbs |
| 954-0638 | 2.5" | 55 | 2.75" | 10.75" | 4.125" | 5.875" | 7.25" | 86 lbs |
| 954-0639 | 3" | 85 | 3.25" | 13.75" | 4.875" | 6.75" | 7.625" | 119.5 lbs |
| 954-0640 | 3.5" | 120 | 3.75" | 5.75" | 2.125" | 8.125" | 9.5" | 250 lbs |
| 954-0641 | 4" | 150 | 4.25" | 6.625" | 2.312" | 9" | 10.75" | 358 lbs |







| DCD Box x | DCD Box x Clevis Swivels | | | | | | | | | | |
|-----------|--------------------------|--------|-------|------|-------|--------|---------|--------|--------|------------------|------|
| Part # | Α | В | C | D | E | F | G | н | J | Box Thread | Tons |
| 954-0612 | 10.75" | 6" | 3.25" | 2.5" | 4.75" | 2.875" | 35" | 7.5" | 6.625" | 4.5" IF | 110 |
| 954-0613 | 10.75" | 6.5" | 3.5" | 3" | 5.5" | 3" | 38" | 7.5" | 6.625" | 4.5" IF | 165 |
| 954-0614 | 12.5" | 7" | 4" | 3.5" | 6.5" | 4" | 41.875" | 8.25" | 7.75" | 6.625" Reg | 220 |
| 954-0647 | 14.5" | 8.562" | 4.5" | 4" | 7" | 3.5" | 2.437" | 8.437" | 8.5" | 6.625" Full Hole | 275 |
| 954-0615 | 16" | 9" | 5" | 4.5" | 8.5" | 4.5" | 50.687" | 9.25" | 9.25" | 6.625" Full Hole | 350 |
| 954-0616 | 19.5" | 10.5" | 5.5" | 5.5" | 9.75" | 5.25" | 55.562" | 9.25" | 9.25" | 6.625" Full Hole | 500 |
| 954-0618 | 19.5" | 10.5" | 5.5" | 5.5" | 9.75" | 5.25" | 55.562" | 8.875" | 8.5" | 7.625" Reg | 500 |
| 954-0619 | 23" | 12.5" | 6.5" | 6.5" | 11.5" | 5.5" | 65.437" | 9.5" | 9.25" | 7.625" Reg | 700 |



REPAIR PARTS & MAINTENANCE

| Pump Parts | Pump Parts (Valve Kit, Packing Kit & Ceramic or Stainless Cylinder | | | | |
|--|--|--|--|--|--|
| Part # | Description | | | | |
| 954-0515 | 954-0515 1432 Value Kit | | | | |
| 954-0516 | 954-0516 1432 Packing Kit | | | | |
| 954-0514 4" Ceramic Cylinder | | | | | |
| *Pump parts provided for Kerr, Myers Aplex, FMC and Ellis Williams Units | | | | | |

Vice Jaws

| Recycler Par | Recycler Parts (Screens, Hydrocones, & Aluminium or Ploypropylene) | | | | |
|--------------|--|-------------------------------|--|--|--|
| Part # | Size | Description | | | |
| 954-0620 | 49" x 25" | Cobra Screen | | | |
| 954-0484 | 46.5" x 28" x 1.25" | Flomax Black Metal 70 Screen | | | |
| 954-0485 | 46.5" x 28" x 1.25" | Flomax Black Metal 140 Screen | | | |
| 954-0621 | 24" x 36" | Triflow Jay Hook Style Screen | | | |

* Recycler Parts provided for Triflo, Mudtech, Kemtron, Derrick and American Auger Units



| Part # | Item | Description | |
|----------|----------|---|-----------|
| 954-0571 | Vice Jaw | 4.125" Contour V-Die Jaw Insert - DD6 (New Style) | |
| 954-0573 | Vice Jaw | .375" x 1" X 4.25" Jaw Insert - DD70, DD100, Astec 3238 | |
| 954-0575 | Vice Jaw | 2.5" x .79" x 2" Jaw Insert - DD5, DD6 (Old Style) | |
| 954-0574 | Vice Jaw | Jaw Insert - DD70, DD100 | |
| 954-0094 | Vice Jaw | 3.875" x 1.25" x .5" Jaw Insert - VM D50/100, D80/100 - Uni 160/240 & DD110 | |
| 954-0457 | Vice Jaw | 3.875" x 1.25" x .5" Diamond Pt Jaw Insert - VM D50/100, D80/100 - Uni 160/240, DD111 | |
| 954-0578 | Vice Jaw | 5.875" x 1.25" x .5" Jaw Insert - VM VM 330/550 | |
| 954-0576 | Vice Jaw | 3" x 1.25" x .5" Jaw Insert - DD180 | ARRE LEAR |
| 954-0577 | Vice Jaw | .5" x 1.25" x 2.5" Jaw Insert - DD6 | |
| 954-0572 | Vice Jaw | 5.875" x 1.25" x .75" Jaw Insert - VM VM 330/550 | |
| 954-0579 | Vice Jaw | 5.875" x 1.25" x 1" Jaw Insert - VM VM 330/550 | |
| 954-0644 | Vice Jaw | 3.875" x 1.25" x .75" Jaw Insert - VM D50/100, D80/100 - Uni 160/240 & DD110 | |
| 954-0645 | Vice Jaw | 3.875" x 1.25" x 1" Jaw Insert - VM D50/100, D80/100 - Uni 160/240 & DD110 | |
| 954-0646 | Vice Jaw | 5" x 1.25" x .5" Jaw Insert - AA440T | |

| Grease | | |
|----------|---------------|------------------------------|
| Part # | Item | Description |
| 954-0069 | Kopr-Kote | JL Kopr-Kote Thr Lube, 5 Gal |
| 954-0448 | Kopr-Kote Eco | JL Eco-Safe Thr Lube, 5 Gal |
| 954-0549 | Dope Brush | 30" OAL |

| Rod Wipers | | |
|------------|----------------------|------------------|
| Part # | Item | Description |
| 954-0473 | Dual Split Rod Wiper | 3.5" ID x 14" OD |
| 954-0474 | Dual Split Rod Wiper | 4" ID x 14" OD |
| 954-0475 | Dual Split Rod Wiper | 4.5" ID x 14" OD |
| 954-0476 | Dual Split Rod Wiper | 5" ID x 14" OD |
| 954-0477 | Dual Split Rod Wiper | 6" ID x 14" OD |

| 954-0402 CT-Silver Lithium Supercell 954-0403 CT-Blue Lithium | Batteries Part # | Item | |
|---|------------------|----------------------------|----------|
| 954-0403 CT-Blue Lithium | | | |
| | | • | |
| 954-0404 Ni-CD Rechargeable Rattery | 954-0403 | CT-Blue Lithium | |
| 11-00 neenargeable Dattery | 954-0404 | Ni-CD Rechargeable Battery | 1 |
| 954-0175 AA Batteries | 954-0175 | AA Batteries | |



| CETCO Poly | ymers / Additives | | |
|------------|-------------------|--|--|
| Part # | Item | Description | |
| 954-0580 | Super Gel X | High Yield Bentonite 200 bbl, 50 lb Bags | |
| 954-0440 | Hydraul-EZ | HDD Drilling Fluid Polymer Based Bentonite, 50 lb Bags | CLAY CUTTER |
| 954-0581 | DRILL-TERGE | Wetting Agent, 5 Gal Pail | Representation of the second s |
| 954-0582 | INSTA-VISPLUS | Liquid Drilling Polymer, 5 Gal Pail | El a constante del la constante El a constante del la constante El a constante del la constante El a constante del la constante del constante del la constante |
| 954-0583 | CLAYCUTTER | Clay Inhibitor, 5 Gal Pail | |
| 954-0584 | SUPERTHIN | Drilling Fluid Thinner, 5 Gal Pail | NET CONTENTS: 42 LBS |
| 954-0585 | SODA ASH | Sodium Carbonate, PH Balancer | |

JOB SITE ACCESSORIES & SAFETY

Contractor supply houses are not always close when you need them. Fortunately we are! Radius stocks a complete line of popular HDD accessories and safety equipment to keep your jobsite running smooth. Don't see what you need? Call us. Odds are very good we can get it – fast!

| Di-Electric gear | | |
|------------------|-------------------------|---------------|
| Part # | Item | Description |
| 954-0652 | Servus Dielectric Boots | Size 8 |
| 954-0653 | Servus Dielectric Boots | Size 9 |
| 954-0654 | Servus Dielectric Boots | Size 10 |
| 954-0655 | Servus Dielectric Boots | Size 11 |
| 954-0656 | Servus Dielectric Boots | Size 12 |
| 954-0657 | Servus Dielectric Boots | Size 13 |
| 954-0658 | Linemans Glove Kits | Size 8 11" L |
| 954-0659 | Linemans Glove Kits | Size 9 11" L |
| 954-0660 | Linemans Glove Kits | Size 10 11" L |
| 954-0661 | Linemans Glove Kits | Size 11 11" L |
| 954-0662 | Linemans Glove Kits | Size 8 14" L |
| 954-0663 | Linemans Glove Kits | Size 9 14" L |
| 954-0664 | Linemans Glove Kits | Size 10 14" L |
| 954-0665 | Linemans Glove Kits | Size 11 14" L |

| Flame Resistant gear | | |
|----------------------|---------------------------|--------------------------|
| Part # | Item | Description |
| 954-0671 | Flame Resistant Coveralls | Royal Blue, Size Small |
| 954-0672 | Flame Resistant Coveralls | Royal Blue, Size Medium |
| 954-0673 | Flame Resistant Coveralls | Royal Blue, Size Large |
| 954-0674 | Flame Resistant Coveralls | Royal Blue, Size X-Large |
| 954-0675 | Flame Resistant Coveralls | Royal Blue, Size 2XL |
| 954-0676 | Flame Resistant Coveralls | Royal Blue, Size 3XL |
| 954-0723 | Flame Resistant Gloves | Medium |
| 954-0724 | Flame Resistant Gloves | Large |
| 954-0725 | Flame Resistant Gloves | XL |
| 954-0726 | Flame Resistant Gloves | 2XL |





| Pipe Tongs | & Accessories | | |
|------------|------------------------------|-----------------------------|-------|
| Part # | Item | Description | |
| 954-0703 | Petol Drill Pipe Tongs Only | 3" - 8.25", 36" Handle | |
| 954-0704 | Petol Special Chain Complete | 7.25" - 8.25" OD | |
| 954-0705 | Petol Drill Pipe Tongs Only | 4.25" - 10.75", 36" Handle | |
| 954-0706 | Petol Special Chain Complete | 9.875" - 10.75" OD | |
| 954-0707 | Petol Drill Pipe Tongs Only | 4" - 14", 36" Handle | |
| 954-0708 | Petol Special Chain Complete | 13.75" - 14" OD | |
| 954-0709 | Petol Bukup Tongs Only | 4.25" - 10.75", 48" Handle | |
| 954-0710 | Petol Bukup Special Chain | Complete, 9.5" - 10.75" OD | 2 |
| 954-0711 | Petol SLM Grip Tongs | 1" - 2.25" OD, 16" Handle | |
| 954-0712 | Petol SLM Grip Tongs | 2.375" - 4" OD, 28" Handle | |
| 954-0713 | Petol SLM Grip Tongs | 3.75" - 6.5" OD, 33" Handle | NO SE |

| Job Site & | Safety | |
|------------|------------------------------------|---|
| Part # | Item | Description |
| 954-0197 | First Aid Kit | Small Auto First Aid Kit |
| 954-0648 | Large First Aid Kit | Large 25 Person First Aid Kit |
| 954-0649 | Fire Extinguisher | B & C Fire Extinguisher, 10lb Potassium Bicarbonate |
| 954-0650 | Fire Extinguisher | B & C Fire Extinguisher, 20lb Potassium Bicarbonate |
| 954-0651 | Fire Extinguisher | B & C Fire Extinguisher, 4lb Sodium Bicarbonate |
| 954-0157 | Marking Flags | (100 PK) Green Neon |
| 954-0158 | Marking Flags | (100 PK) Pink Neon |
| 954-0317 | Marking Flags | (100 PK) Red |
| 954-0318 | Marking Flags | (100 PK) White |
| 954-0319 | Marking Flags | (100 PK) Green Neon |
| 954-0177 | Safety Netting | Orange Mesh 4' x 100' |
| 954-0178 | Safety Tape (Caution) | Yellow/Black 300' x 3" |
| 954-0180 | Safety Tape (Caution) | Yellow/Black 1000' x 3" |
| 954-0179 | Safety Tape (Danger) | Red/Black 1000' x 3" |
| 954-0172 | 3 Gallon Water Cooler | Rubbermaid (Orange) |
| 954-0171 | 10 Gallon Water Cooler | Rubbermaid (Orange) |
| 954-0176 | Traffic Cones | Orange / 28" H / 14" Base |
| 954-0190 | Safety Glasses - Amber | Crews Brand |
| 954-0191 | Safety Glasses - Gray | Crews Brand |
| 954-0192 | Safety Glasses - Clear | Crews Brand |
| 954-0193 | Safety Glasses - Mirror | Crews Brand |
| 954-0194 | Safety Glasses - Green | Crews Brand |
| 954-0195 | Safety Glasses - In/Outdoor | Crews Brand |
| 954-0187 | Back Support | Large - Black |
| 954-0188 | Back Support | XL - Black |
| 954-0189 | Back Support | XXL- Black |
| 954-0666 | Ear Plugs | Moldex w/ Cord Box -100 Pairs NRR 33db |
| 954-0220 | Safety Vest | Q - TWO Tone S/M |
| 954-0221 | Safety Vest | Q - TWO Tone L/XL |
| 954-0222 | Safety Vest | Q - TWO Tone 2XL/3XL |
| 954-0223 | Safety Vest | Orange - Safety Vest LG |
| 954-0224 | Safety Vest | Orange - Safety Vest XL |
| 954-0225 | Safety Vest | Orange - Safety Vest 1 Size fits All |
| 954-0667 | Disposable Respirators | Moldex (Dirt Dawgs) Particulate Respirators |
| 954-0668 | Halfmask Cartridge Respirators | 3M |
| 954-0669 | Respirator Cartridges | 3M (Fits 954-0668 Respirators) |
| 954-0670 | Respirator Filters | 3M (Fits 954-0669 Cartridges) |
| 954-0181 | Full Brim High Visability Hard Hat | Fluorescent Yellow |
| 954-0349 | Full Brim High Hard Hat | Orange |
| 954-0350 | Full Brim High Hard Hat | White |
| 954-0186 | Standard Hard Hat | Yellow |
| 954-0182 | Standard Hard Hat | White |
| | | 1 |















Radius Maxi Rig Tooling and Supplies

MAXI. NO PROBLEM.

RIG NOTES & REFERENCE NUMBERS

| |
|------|
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |

