



ZAHN

TOOL CARRIER AND VIBRATORY PLOW



Ditch Witch
R300

Standard cruise control, which locks in operating speeds, reduces operator fatigue and increases productivity.

Soft-touch, color-coded controls are easy to grip and provide smooth operation.

1

2

3

Convenient cargo tray for storing water bottle, work gloves, cell phone or assorted tools.

8

Robust, 27-hp (20.1-kW) Kohler® engine maximizes front-end productivity.

7

6

Roomy ride-on platform absorbs shock, reduces fatigue and keeps you out of dirt, mud and debris.



ZAHN

Fully hydraulic, articulated steering provides unmatched maneuverability, enabling you to easily trench a curve.

The innovative design of the Zahn R300 tool carrier means you don't have to sacrifice power for versatility. With both the high- and low-lift models, you'll get maximum productivity from the dozens of available quick-change compact utility attachments. But the versatility doesn't cost you anything in performance, with a unique InterChange™ connection that lets the front end become the machine and perform like a dedicated unit.

4

Compact design for maneuvering in tight jobsites.

5

Optional high flotation tires distribute weight evenly to minimize impact on lawns and other delicate turf, optional tracks increase stability and performance.

ZAHN

ATTACHMENTS



TOOL CARRIER

- 73-inch (1.85-m) hinge pin height provides the flexibility to perform an extensive range of tasks.
- Roomy, ride-on platform absorbs shock, reduces fatigue and keeps you out of dirt, mud and debris.
- Dual-element remote air cleaner provides outstanding filtration even in dusty conditions.
- Optional self-leveling kit—an exclusive feature—ensures that the attachment is level, so work can be more accurate and efficient.
- Kickstand for quick and easy attachment to and removal from the power unit.
- Exclusive traction-assist feature provides extra drawbar on demand, enabling you to push more, pull more and traverse soft ground with minimal tire slippage.
- 4-bar linkage on bucket curl increases rollback and dump angles so you can move materials more efficiently.
- Standard attachment plate provides maximum versatility; accepts more than 40 quick-change attachments.

DIMENSIONS

U.S.

METRIC

Mobile length	91.5 in	2.32 m
Tie-down length	29.8 in	757 mm
Length, max	91.5 in	2.32 m
Attachment length	45.7 in	1.16 m
Mobile height	53.5 in	1.36 m
Tie-down height	46.1 in	1.17 m
Attachment height, max	81.8 in	2.08 m
Bucket height, max	96 in	2.44 m
Hinge pin height	73 in	1.85 m
Dump clearance	55.5 in	1.41 m
Width	36 in	914 mm
Attachment width	23 in	584 mm
Angle of departure	25°	
Dump angle	53°	
Rollback angle	18°	
Unit mass	1,889 lb	856.8 kg
Attachment mass	373 lb	169 kg
Tipping capacity	864 lb	391.9 kg
Rated operating capacity (50% of tipping capacity)	432 lb	196 kg

Specifications are general and subject to change without notice. If exact measurements are required, equipment should be weighed and measured. Due to selected options, delivered equipment may not necessarily match that shown.



VIBRATORY PLOW

- Variable blade pitch allows operator to change the angle of the leading edge of the blade to be more or less aggressive, to match soil conditions.
- Accepts standard Ditch Witch® vibratory plow blades, eliminating the need to purchase new blades.
- Optional reel carrier provides efficient installation of cable with minimal jobsite restoration.
- Optional sod cutter and skid shoes provide greater versatility and minimize restoration.
- Ergonomically designed operator's station features soft-touch, color-coded controls that are easy to learn and provide smooth, easy operation.
- 9-gallon (34.06-L) fuel tank enables you to work long hours without having to refuel; the tank's molded-in sight glass allows you to keep an eye on fuel consumption.
- Convenient cargo tray is large enough to store a water bottle, work gloves, cell phone, or assorted tools.
- Optional quad tracks for maximum stability and performance.

DIMENSIONS

	U.S.	METRIC
Mobile length	104.8 in	2.66 m
Tie-down length	101.8 in	2.59 m
Attachment length	55.5 in	1.41 m
Mobile height	56 in	1.42 m
Tie-down height	43 in	1.09 m
Attachment height, max	56 in	1.42 m
Operating depth	20 in	508 mm
Cover depth	18 in	457 mm
Width	36 in	914 mm
Attachment width	18 in	457 mm
Angle of departure	25°	
Angle of approach	30°	
Unit mass	1,839 lb	834.2 kg
Attachment mass w/blade	348 lb	157.9 kg

OPERATION

Plow vibrator force @ 1,600 rpm	4,600 lb	20.46 kN
Material diameter, max		
Pulled	3 in	76 mm
Fed	1 in	25 mm

Specifications are general and subject to change without notice. If exact measurements are required, equipment should be weighed and measured. Due to selected options, delivered equipment may not necessarily match that shown.



TRENCHER

- Accepts two types of trencher front ends, both of which concentrate weight on the digging chain so it can penetrate the ground easier.
- Hydraulic auger that runs independent of the headshaft (patent-pending feature) is standard on 4WD trenchers, optional on 2WD models; this feature reduces the amount of carryover, increasing productivity.
- Hydraulic drive eliminates maintenance of chains, belts and linkages, and allows the use of a reversible digging chain that dislodges rocks and other debris without manual assistance.
- High-performance, 27-hp (20.1-kW) Kohler® engine enables truly dedicated trenching performance.
- Two-wheel-drive models accept chains up to 8 inches (203 mm) wide; 4WD model accepts up to a 12-inch (305-mm) chain, so you can dig trenches for virtually any application.
- Choice of 18-inch (457-mm) or 20-inch (508-mm) urethane-filled, flat-proof tires, provide heavy-duty performance, stability and minimal tire deflection under load.
- Optional quad tracks for maximum stability and performance.

ZAHN R300 TRENCHER

DIMENSIONS	4-WHEEL DRIVE		HEADSHAFT AUGER		INDEPENDENT AUGER	
	U.S.	METRIC	U.S.	METRIC	U.S.	METRIC
Mobile length	126 in	3.2 m	90.5 in	2.3 m	90.5 in	2.3 m
Length, max	142.8 in	3.63 m	104.5 in	2.65 m	104.5 in	2.65 m
Attachment length	58.5 in	1.49 m	58.5 in	1.49 m	58.5 in	1.49 m
Wheelbase	34.2 in	869 mm	44.2 in	1.12 m	44.2 in	1.12 m
Mobile height	65 in	1.65 m	53.5 in	1.36 m	53.5 in	1.36 m
Tie-down height	30.5 in	775 mm	31.7 in	805 mm	31.7 in	805 mm
Attachment height, max	101 in	2.57 m	49.3 in	1.25 m	49.3 in	1.25 m
Operating depth, max	48 in	1.22 m	36 in	914 mm	36 in	914 mm
Width	36 in	914 mm	36 in	914 mm	36 in	914 mm
Cutting width	4-12 in	102-305 mm	4-8 in	102-203 mm	4-8 in	102-203 mm
Spoils width	16 in	406 mm	13.8 in	351 mm	16 in	406 mm
Centerline of trench, left	14 in	356 mm	18.5 in	470 mm	18.5 in	470 mm
Centerline of trench, right	22 in	560 mm	17.5 in	445 mm	17.5 in	445 mm
Attachment width	30.5 in	775 mm	34 in	864 mm	33 in	838 mm
Angle of departure	25°		25°		25°	
Attachment travel, down (recommended)	60°		60°		60°	
Attachment travel, up (recommended)	40°		50°		50°	
Unit mass	1,953 lb	885.9 kg	1,438 lb	652.3 kg	1,488 lb	674.9 kg
Attachment mass w/36-in boom and 8-in chain	462 lb	209.6 kg	420 lb	190.5 kg	440 lb	199.6 kg

HEADSHAFT SPEEDS @ 3,600 RPM ENGINE

Low speed/high torque	186 rpm		186 rpm		186 rpm	
Medium speed/medium torque	244 rpm		244 rpm		244 rpm	
High speed/low torque	282 rpm		282 rpm		282 rpm	

POWER TRAIN

Digging chain drive	Hydraulic direct drive		Hydraulic direct drive		Hydraulic direct drive	
Digging chain	33,000 lb or 35,000 lb		33,000 lb or 35,000 lb		33,000 lb or 35,000 lb	
Spoils handling drive	Hydraulic, independent		Hydraulic, independent		Hydraulic, independent	
Chain drive sprocket	Forged and tempered		Forged and tempered		Forged and tempered	

OPERATION

Digging chain speed						
Min	230 ft/min	70.1 m/min	290 ft/min	88.4 m/min	230 ft/min	70.1 m/min
Max	290 ft/min	88.4 m/min	364 ft/min	111 m/min	364 ft/min	111 m/min
Trench cleaner type, mechanical						
Min	4 in	102 mm	4 in	102 mm	4 in	102 mm
Max	12 in	305 mm	8 in	203 mm	8 in	203 mm
Spoils handling	Single open end auger		Single open end auger		Single open end auger	
Auger size	6.18-in OD x 2-in ID x 17.25-in long		18-in OD x 2-in ID x 8.7-in long		6.18-in OD x 2-in ID x 17.25-in long	

TIRES/PRESSURE

Urethane-filled trail wheel	N/A	N/A	16 x 6.5-8, ply, bar lug		16 x 6.5-8, ply, bar lug	
Tire assembly mass	N/A	N/A	18 lb	8.16 kg	18 lb	8.16 kg

ZAHN R300 PLOW

DIMENSIONS

	U.S.	METRIC
Mobile length	70 in	1.78 m
Wheelbase	34.2 in	869 mm
Tractor back to rear axle	26.8 in	681 mm
Rear axle to attachment mounting	19.2 in	488 mm
Attachment mounting to front axle	15 in	381 mm
Mobile height	53.5 in	1.36 m
Ground clearance	5.3 in	135 mm
Platform height	10.7 in	272 mm
Width	36 in	914 mm
Angle of departure	25°	
Weight w/tires	1,290 lb	585 kg
Weight w/tracks	1,629 lb	738 kg
Mass	1,290 lb	585 kg
Vehicle clearance circle (SAE) wall to wall		
Right turn, 18 x 9.5-8 tires	11.3 ft	3.44 m
Left turn, 18 x 9.5-8 tires	10.5 ft	3.2 m
Right turn, tracks	15.8 ft	4.80 m
Left turn, tracks	16.7 ft	5.08 m

OPERATION

Ground drive speed, forward/reverse		
Low	3.5 mph	5.6 km/h
High	5 mph	8 km/h

HYDRAULIC SYSTEM

Auxiliary: gear pump		
Flow rate	12 gpm	46 l/min
Pressure	3,000 psi	207 bar
Ground drive: hydrostat		
Flow rate	19.3 gpm	73 l/min
Pressure	3,500 psi	241 bar
Ground pressure		
18 x 9.5-8 tires	10 psi	.7 bar
20 x 10-8 tires	9 psi	.6 bar
Tracks, averaged	3.11 psi	.21 bar

POWER

	U.S.	METRIC
Engine	Kohler® CH750S	
Fuel	Gasoline	
Cooling medium	Air	
Number of cylinders	2	
Displacement	45.6 in ³	747 cm ³
Bore	3.3 in	83 mm
Stroke	2.7 in	69 mm
Manufacturer's power rating	27 hp	20.1 kW
Rated speed	3,600 rpm	

POWER TRAIN

Parking brake	Mechanical, hand operated
Service brake	Ground drive speed/direction control brakes machine hydraulically when moved to neutral position

FLUID CAPACITIES

Fuel tank	9 gal	34.06 L
Engine oil, w/filter	2 qt	1.9 L
Hydraulic reservoir	7.7 gal	29.1 L
Total hydraulic system volume	8.5 gal	32.2 L

TIRES/PRESSURE

Urethane filled 18 x 9.5-8, 2 ply, bar lug	N/A	
Tire assembly mass	36 lb	16.33 kg
Urethane filled 20 x 10-8, ply, bar lug	N/A	
Tire assembly mass	49 lb	22.23 kg

BATTERY

SAE reserve capacity rating	32 min
SAE cold crank rating (@ 0°F [-18°C])	200 amps

Specifications are general and subject to change without notice. If exact measurements are required, equipment should be weighed and measured. Due to selected options, delivered equipment may not necessarily match that shown.

