

# HAMMERHEAD®

TOUGH. TRUSTED.



**HAMMERHEAD®**  
TRENCHLESS EQUIPMENT

LEADING THE INDUSTRY WITH THE PATENTED SELF DEPLOYING BOOM  
**HYDROGUIDE® HG12**

HAMMERHEAD® HYDROGUIDE® HG12

# AUTO BOOM PIPE BURSTING WINCH



## PATENTED SELF DEPLOYING DOWNRIGGER

The HydroGuide HG12 winch has an industry first patented self deploying downrigger. Simplification through automation. The hydraulic self deploying down rigger simplifies setup and eliminates carrying large and heavy components down hole. The infinitely adjustable boom can easily be set to the depth required without jacking up the machine.

## MINIMUM SETUP TIME, MAXIMUM EFFICIENCY

The HG12 winch is designed to maximize efficiency and minimize setup time and effort for your trenchless projects. Setup and tear-down can be done in minutes, not hours. The bottom line is less labor and more profit. Remote control and a powerful down hole light put the operator in better control of the burst process.

## PROVEN BULLWHEEL AND PLANETARY DRIVE SYSTEM

The solid dual capstan design offers constant pulling force over the entire cable length and helps reduce cable wear. The bullwheel and planetary drive system provides reliability on the job, where it counts.

## PERFORMANCE ENHANCING OPTIONS

Hydraulic leveling jacks are infinitely adjustable and increases efficiency at the end of your manhole exit projects. The HG12AT track mounted winch reaches difficult areas on your jobsite where others can't.



HYDROGUIDE HG12AT

## EQUIPMENT SPECIFICATIONS

HYDROGUIDE® HG12	Rig Size L/W/H – in (m)	171/70/67 (4.34/1.78/1.69)
	Weight – lb (kg)*	6,002 (2,722)
	Max. pulling force – tons (t)	12 (11)
	Max. Line Speed – fpm (mpm)**	47 (14.3)
	Engine Manufacturer/Model	Kubota V1505, Diesel
	Cooling System	Water cooled
	Engine – HP (kw)	36 (26.5)
	Downrigger Length – ft (m)	18 (5.49)
	Cable Diameter – in (mm)	.625 (16)
	Cable Weight – lb (kg)	1,498 (679)
	Cable Capacity – ft (m)***	2,080 (634)

FEATURES	Hydraulic Downrigger	Standard
	Multi Position Leveling Jacks	Standard, manual (1 front, 2 rear)
	Hydraulic Leveling Jacks	Optional, (1 front, 2 rear)
	Remote Hydraulics	Standard
	Downrigger Light	Standard
	Electric Start	Standard
	Auxillary Hydraulic Connection	Standard
	All Terrain Track Mount	Available on the HG12AT
	Downrigger Mast Extension	Optional

\*Weight without cable and/or optional accessories. \*\*Line speed automatically adjusts to burst speed. \*\*\*Usable cable length of 2,000 ft (610 m).

# CALL 800.331.6653

## FOR A FREE PROJECT CONSULTATION TODAY.

800.331.6653 (USA only) | international: +1 262.567.8833 | web: [www.hammerheadtrenchless.com](http://www.hammerheadtrenchless.com) | email: [info@hammerheadmole.com](mailto:info@hammerheadmole.com)

Earth Tool Company LLC reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacture at any time without notice or obligation. HAMMERHEAD, HAMMERHEAD LOGO and HYDROGUIDE are registered trademarks of Earth Tool Company LLC, Oconomowoc, WI. PN: L240-04123K ©2013 Earth Tool Company LLC. All Rights Reserved.

