


A AMERICAN AUGERS®

DD-240T



- 240,000 lbs. (120 Tonnes) Thrust//Pullback
- 43,900 ft. lbs. of rotary torque at 37 rpm
- Full length traveling wrenches
- On Board/Off Board cabin configurations
- Flexible Operator Control settings for reduced training time
- Optional feature configurations for your specific package needs
- 523 hp MTU Tier 4f engine (No Regen) and Tier 3 for non-regulated areas
- 20 ft. or Range 2 Drill Frame Lengths

The fully configurable rig built for modern day job requirements.



DD-240T

Weights & Dimensions

Length:	52.6 ft. (15.08 m)
Height:	133 in. (3.37 m)
Width:	98.4 in. (2.5 m)
Transport Weight:	84,600 lb. (38,373 kg)

Engine

Make/Model:	MTU (Mercedes)
Fuel Type:	Ultra-low sulfur diesel
Max engine rpm:	1900
Horsepower:	523 (390 kW)
Emissions rating:	Tier 4 Final or Tier 3 where applicable
No Regen Cycle	

Operation

Thrust/Pullback:	240,000 lbs. (120 tonnes)
Max carriage speed:	150 ft./minute (45.72 mpm)
Working Torque:	43,900 ft. lbs. @ 37rpm (59,590 Nm)
Max Rotary Speed:	150 rpm
Max Breakout Torque (Wrench):	80,000 ft. lbs. (108,465 Nm)
Max Travel Speed:	1.4 mph forward & reverse (2.25 kph)

Fluid Capacities

Fuel:	180 U.S. Gallons (681 L)
Hydraulic:	120 U.S. Gallons (454 L)

Pump

Max Flow:	300 U.S. Gallons/minute (1,135 lpm)
Max Pump Pressure:	1,109 psi (76.5 bar)
Max Fluid Stream Pressure:	1,300 psi (89.6 bar)

Suggested Parts

Item	Description
TBD	

Pair with the M-300D from American Augers for maximum performance.



AmericanAugers.com

135 US Route 42 · PO BOX 814 · West Salem, OH 44287 · Phone +1.419.869.7107 · Fax +1.419.869.7425